

Certus

making your products safer



LCD/LED Interface

Easy-to-use interface employs a membrane key pad with LCD/LED screen.



Conveyor System

Certus is available with either a heavy duty or standard duty stainless steel conveyor system

Cost-Effective, User-Friendly Metal Detection

The new METTLER TOLEDO Safeline Certus provides highly reliable, cost-effective metal detection in dry applications. The stainless steel unit offers high sensitivity with automatic product set up and an easy to use LCD/LED display with a membrane key pad.

The easy-to-use Certus is the ideal way to implement metal detection in order to protect your products and grow your customer base. Certus is designed for use in non-wash down applications.

Certus Metal Detector

The Certus provides highly reliable METTLER TOLEDO Safeline metal detection technology in non wash down applications. Standard features include:

- **Stainless steel case**
- **User-friendly LCD/LED display with membrane key pad**
- **Automatic product set up**
- **Two serial ports for connectivity and reporting**
- **Product setting memory**

Certus can be purchased as a stand-alone metal detector head or with a fully-integrated conveyor system with optional product reject mechanisms. METTLER TOLEDO Safeline offers both heavy duty and standard duty stainless steel construction conveyor systems depending on your product weights - contact sales for more information.

Certus Metal Detector Specifications

Construction	Stainless Steel
Protection rating	IP54, NEMA 13
Electrical Supply	100 to 240 Volts A.C., 50 to 60 Hz
Approvals	UL and cUL (UL61010A-1. c22.2 no 61010.1-92) CE: LVD (EN61010-1 :2001) EMC (Emissions EN 61000-6-3 ; 2001, Immunity EN 61000-6-2 ; 2001)
Manufacturing	ISO9001 : 2000
User Interface	Membrane key panel and LCD / LED displays
Connectivity	Two RS232 compatible serial ports

Conveyor System Specifications

Max Product Weights	Heavy duty systems up to 250lbs; weights over 250lbs, contact the Safeline sales office
Belt Types	Plastic, tabletop chain, fabric and vinyl options
Belt width	2" - 60" in 1" increments
Reject Options	Stop belt, air blast, pusher, bi-directional overhead sweep, retracting nose, end flap, drop nose and sweep arm. Standard and customized options available
System Standards	BISSC Third Party Verified; 3A Dairy Certified; USDA Compliant

Safeline - making your products safer.



Mettler-Toledo Safeline, Inc.

6005 Benjamin Road, Tampa, FL 33634

Toll Free 800 447-4439

Tel: 813-889-9500

Fax: 813-881-0840

Email: safeline.sales@mt.com



Subject to technical changes

© 2006 Mettler-Toledo Safeline, Inc.

Printed In the U.S.A.

SLMD-US-DSE-Certus-06-00M

www.safelineus.com

Visit for more information